| lie⊍≤nia J _ | 114/ |
|---------------------|------|
| FOLLOW UF | |
| PRODEED L | |

FILED DENISON, IOWA CRAWFORD COUNTY

2004 JAN 26 AM 11: 48

INST. NO 2004-0224
DENISE MEEVES. RECORDER

DONING MEEVES
FEE 11,00

WARDER C. HILLHOUSE, JR. MHF ENGINEERING P.C. 300 W. McKINLEY JEFFERSON, IA. (515)386-4101

| (Show reason for preparing this certificate, the evidence and detailed procedures used in establishing the corner positions and monumentation found or placed.) Monument Description and Remarks: CORNERS LOCATED FOR SURVEY WORK IN SECTION. PLAN — VIEW (Show a minimum of three reference ties to durable physical objects, relevant monuments and physical conditions that will enable recovery of the corner.) WI/4 COR 28-85-37 CENTER 28-85-37 CORNER POST OCORNER | UNITED STATES PUBLIC LAI Land Survey Monuments in Section 37, of the Fifth Principa Previously recorded in | 28 , Township 85 , Range al Meridian, CRAWFORD County, Iowa. in County Recorder's Office. |
|--|--|--|
| Monument Description and Remarks: CORNERS LOCATED FOR SURVEY WORK IN SECTION. PLAN - VIEW (Show a minimum of three reference ties to durable physical objects, relevant monuments and physical conditions that will enable recovery of the corner.) WI/4 COR 28-85-37 CENTER 28-85-37 ** NAILS TOP BRACE POST 2842.72* 10.85* 2597.36* ** NAILS TOP SIGN POST 2842.72* 2597.36* ** SET 1/2* REPROD TOP OF SILDR 2842.72* 2597.36* ** SET 1/2* REPROD TOP OF SILDR 2842.72* 2842 | (Show reason for preparing this certificate, | the evidence and detailed procedures used in establishing |
| (Show a minimum of three reference ties to durable physical objects, relevant monuments and physical conditions that will enable recovery of the corner.) W1/4 COR 28-85-37 CENTER 28-85-37 CENTER 28-85-37 CENTER 28-85-37 CORNER POST 2842.72' ACCEPTED EXISTING INTERSECTION OF FENCES NORTH, EAST AND WEST AS CENTER OF SECTION WHICH POINT IS APPROXIMATELY 16' EAST AND 8' SOUTH FROM THE POINT OF INTERSECTION OF LINES FROM THE WI/4 COR. TO E1/4 COR. SET 5/8/X30'REROD WITH YELLOW SW COR 28-85-37 CENTER 05 TO SISTING INTERSECTION OF FENCES NORTH, EAST AND WEST AS CENTER OF SECTION WHICH POINT IS APPROXIMATELY 16' EAST AND 8' SOUTH FROM THE POINT OF INTERSECTION OF LINES FROM THE WI/4 COR. TO E1/4 COR. SET 5/8/X30'REROD WITH YELLOW CAP/8606. N SW COR 28-85-37 CENTER 05 SCORNER POST ACCEPTED EXISTING INTERSECTION OF FENCES NORTH, EAST AND WEST AS CENTER OF SECTION WHICH POINT IS INTERSECTION OF LINES FROM THE WI/4 COR. TO E1/4 COR. SET 5/8/X30'REROD WITH YELLOW CAP/8606. N SW COR 28-85-37 CENTER 05 SCORNER POST ACCEPTED EXISTING INTERSECTION OF FENCES NORTH, EAST AND WEST AS CENTER OF SECTION WHICH POINT IS INTERSECTION OF LINES FROM THE WI/4 COR. TO E1/4 COR. SET 5/8/X30'REROD WITH YELLOW CAP/8606. N SW COR 28-85-37 CENTER 05 SW COR 28-85-37 SET 1/2* REROD TOP OF SHLDR. F AVENUE | · | • |
| (Show a minimum of three reference ties to durable physical objects, relevant monuments and physical conditions that will enable recovery of the corner.) W1/4 COR 28-85-37 CENTER 28-85-37 CENTER 28-85-37 CENTER 28-85-37 CORNER POST 2842.72' ACCEPTED EXISTING INTERSECTION OF FENCES NORTH, EAST AND WEST AS CENTER OF SECTION WHICH POINT IS APPROXIMATELY 16' EAST AND 8' SOUTH FROM THE POINT OF INTERSECTION OF LINES FROM THE WI/4 COR. TO E1/4 COR. SET 5/8/X30'REROD WITH YELLOW SW COR 28-85-37 CENTER 05 TO SISTING INTERSECTION OF FENCES NORTH, EAST AND WEST AS CENTER OF SECTION WHICH POINT IS APPROXIMATELY 16' EAST AND 8' SOUTH FROM THE POINT OF INTERSECTION OF LINES FROM THE WI/4 COR. TO E1/4 COR. SET 5/8/X30'REROD WITH YELLOW CAP/8606. N SW COR 28-85-37 CENTER 05 SCORNER POST ACCEPTED EXISTING INTERSECTION OF FENCES NORTH, EAST AND WEST AS CENTER OF SECTION WHICH POINT IS INTERSECTION OF LINES FROM THE WI/4 COR. TO E1/4 COR. SET 5/8/X30'REROD WITH YELLOW CAP/8606. N SW COR 28-85-37 CENTER 05 SCORNER POST ACCEPTED EXISTING INTERSECTION OF FENCES NORTH, EAST AND WEST AS CENTER OF SECTION WHICH POINT IS INTERSECTION OF LINES FROM THE WI/4 COR. TO E1/4 COR. SET 5/8/X30'REROD WITH YELLOW CAP/8606. N SW COR 28-85-37 CENTER 05 SW COR 28-85-37 SET 1/2* REROD TOP OF SHLDR. F AVENUE | | |
| (Show a minimum of three reference ties to durable physical objects, relevant monuments and physical conditions that will enable recovery of the corner.) W1/4 COR 28-85-37 CENTER 28-85-37 CENTER 28-85-37 CENTER 28-85-37 CORNER POST 2842.72' ACCEPTED EXISTING INTERSECTION OF FENCES NORTH, EAST AND WEST AS CENTER OF SECTION WHICH POINT IS APPROXIMATELY 16' EAST AND 8' SOUTH FROM THE POINT OF INTERSECTION OF LINES FROM THE WI/4 COR. TO E1/4 COR. SET 5/8/X30'REROD WITH YELLOW SW COR 28-85-37 CENTER 05 TO SISTING INTERSECTION OF FENCES NORTH, EAST AND WEST AS CENTER OF SECTION WHICH POINT IS APPROXIMATELY 16' EAST AND 8' SOUTH FROM THE POINT OF INTERSECTION OF LINES FROM THE WI/4 COR. TO E1/4 COR. SET 5/8/X30'REROD WITH YELLOW CAP/8606. N SW COR 28-85-37 CENTER 05 SCORNER POST ACCEPTED EXISTING INTERSECTION OF FENCES NORTH, EAST AND WEST AS CENTER OF SECTION WHICH POINT IS INTERSECTION OF LINES FROM THE WI/4 COR. TO E1/4 COR. SET 5/8/X30'REROD WITH YELLOW CAP/8606. N SW COR 28-85-37 CENTER 05 SCORNER POST ACCEPTED EXISTING INTERSECTION OF FENCES NORTH, EAST AND WEST AS CENTER OF SECTION WHICH POINT IS INTERSECTION OF LINES FROM THE WI/4 COR. TO E1/4 COR. SET 5/8/X30'REROD WITH YELLOW CAP/8606. N SW COR 28-85-37 CENTER 05 SW COR 28-85-37 SET 1/2* REROD TOP OF SHLDR. F AVENUE | | |
| FOUND AND ACCEPTED BROKEN CONCRETE MONUMENT AND OLD WOODEN HUD 3.5' DEEP, SET 5/8'X30'REROO WITH YELLOW CAP#6806 ABOVE MONUMENT. SW COR 28-85-37 CENTER 28-85-37 CENTER 28-85-37 CENTER 28-85-37 CENTER 28-85-37 CENTER 28-85-37 X' NAILS TOP BRACE POST 2642.72' X' NAILS TOP BRACE POST 2642.72' ACCEPTED EXISTING INTERSECTION OF FENCES NORTH, EAST AND WEST AS CENTER OF SECTION WHICH POINT IS APPROXIMATELY 16' EAST AND 8' SOUTH FROM THE POINT OF INTERSECTION OF INTERSECTI | PI | LAN - VIEW |
| FOUND AND ACCEPTED BROKEN CONCRETE MONUMENT AND OLD WOODEN HUD 3.5' DEEP. SET 5/8'X30'REROD WITH YELLOW CAP#6806 ABOVE MONUMENT. SW COR 28-85-37 CENTER 28-85 | (Show a minimum of three reference ties to conditions that will enable recovery of the | o durable physical objects, relevant monuments and physical corner:) |
| FOUND AND ACCEPTED BROKEN CONCRETE MONUMENT AND OLD WOODEN HUD 3.5' DEEP, SET 5/8'X30'REROD WITH YELLOW CAP#6806 ABOVE MONUMENT. SW CORNER POST 2642.72' X NAILS TOP BRACE POST 2642.72' X NAILS TO | · | |
| STOP SIGN POST | FOUND AND ACCEPTED BROKEN CONCRETE MONUMENT AND OLD WOODEN HUD 3.5' DEEP. SET 5/8"X30"REROD WITH YELLOW CAP#6806 ABOVE MONUMENT. SW COR 28-85-37 CENTER OF WATER VALVE TX NAILS IN STOP SIGN POST TX NAILS IN STOP SIGN POST | "X" NAILS TOP BRACE POST 2642.72' x 10.85' x 2597.36 x ACCEPTED EXISTING INTERSECTION OF FENCES NORTH, EAST AND WEST AS CENTER OF SECTION WHICH POINT IS APPROXIMATELY 16' EAST AND 8' SOUTH FROM THE POINT OF INTERSECTION OF LINES FROM THE N1/4 COR.(FENCE COR.) TO S1/4 COR. AND FROM THE W1/4 COR. TO E1/4 COR. SET 5/8"X30"REROD WTH YELLOW CAP#6806. S1/4 COR 28-85-37 SET 1/2"REROD SET 1/2"REROD |
| FOUND AND ACCEPTED 1" REROD 1' DEEP. FOUND AND ACCEPTED 1" REROD 3" DEEP. | FOUND AND ACCEPTED 1" REROD 1' DEEP. | FOUND AND ACCEPTED 1" REROD 3" DEEP. |
| I hereby certify that this land surveying document and the related survey work was performed by me or under my direct personal supervision and that I am a duly licensed land, surveyor under the laws of the state of lowa Signature: Narde C. Hullhouse, Jr. Date: 1/22/04 Lic. No. 6806 List Corners to be Indexed Corners Section Twp Rang W1/4 COR 28 85 37 SW COR 28 85 37 CENTER 28 85 37 CENTER 28 85 37 | the related survey work was performed by my direct personal supervision and that I ar licensed land, surveyor under the laws of the Signature: Warder C. Hillhouse, Jr. | me or under am a duly Corners Section Twp Rang with the state of Iowa. W1/4 COR 28 85 37 SW COR 28 85 37 S1/4 COR 28 85 37 CENTER 28 85 37 |
| License Renewal Dec. 31, 2005 | License Renewal Dec. 31, 2005 | |
| Date Surveyed: 01/08/04 WARDER C. HILLHOUSE JR. 6806 File No. 03206-1 M.H.F. ENGINEERING, P.C. FAICHERS LAND SUBJECTOR | WARDER HILLHOUSE 6806 | File No. 03206-1 |



M.H.F. ENGINEERING, P.C. ENGINEERS — LAND SURVEYORS Jefferson, Iowa 50129 Ph. (515)386–410